



Portable Ventilator 300Ø


Our 300Ø Portable ventilators are industrial quality ventilators that move 1085 l/s. They have a 500-watt motor that is sealed to prevent dust entry. Some of the many uses include air and fume extraction or fresh air supply.



SPECIFICATIONS

- Portable Ventilator 300Ø 0
- Motor: 230-240VAC 50Hz 0
- Total Motor Wattage: 500 watts 0
- Sound Pressure Level at 3m in dBA: 65 0
- Impellor Construction: Aluminium 0
- 2800 revs per minute 0
- Free Air Fan Performance: 1085 I/s 0
- Impellor Diameter: 300mm diameter 0
- Chrome protection grille 0
- Rubber feet 0

	Features	Benefits
0	1 Speed control	 Increased airflow
0	Handgrip On/Off Switch	 Sturdy and durable
0	Easily moved, complete with power cord and plug	 Easy positioning to direct airflow
0	Lightweight die cast aluminium	 Will handle most environments and suit any décor
0	5m or 10m PVC flexible duct available	• Move wherever it suits you for optimum performance
 1 Year Warranty 		



- 1 Handgrip/On/Off Switch
- 2 Steel plate body zinc plated
- 3 Rubber feet
- 4 Light & durable fan blade
- 5 Aluminous electromotor hub
- 6 Chrome protection grille
- 7 PVC duct
- 8 Spiral steel wire frame duct



AIRFLOW ENGINEERING (SI) LTD I 2, 3 LANGSTON LANE I NORTHCOTE I CHRISTCHURCH I P O BOX 78091 I PEGASUS I CHRISTCHURCH I 7648 PHONE +64 3 365 6278 EMAIL sales@airflo.co.nz WEB www.airflo.co.nz AIRFLOW ENGINEERING HAVE MADE ALL ATTEMPTS TO PROVIDE ACCURATE AND CORRECT INFORMATION FOR THIS DOCUMENTATION, HOWEVER CONTINUING PRODUCT DEVELOPMENT MAY MEAN THE COMPONENTS, SPECIFICATIONS, IMAGES AND DATA MAY VARY FROM THAT OFFERED FOR SALE. AIRFLOW ENGINEERING DOES NOT ACCEPT ANY LABILITY FOR THIS.