Technical Data Sheet



FV200D

ClearAir Exhaust Fan with Ducting

White Fascia


Dimensions

Cut-out size for inlet fascia


247mm


Cut-out size for outlet fascia


155mm











Specifications

Weight 2Kg Colour of front fascia White Housing material ABS

Approval

AS/NZS 3350.2.80:1998 Amdts 1-3 "Electrical Fan"

Features

- Easy to install
- Powerful fan motor due to blade pitch design
- 3 metres of 150mm diameter ducting included
- Allows moisture to be removed to the outside of your home
- 3 year extended warranty

Technical Data Sheet

Product Use

The FV200D is used for the extraction of mist

Typical applications:

- Bathrooms
- Toilets
- Laundries

Environmental Conditions

Operation to IEC 721-3-3
Climatic conditions class 3K5
Temperature 0...+50°C
Humidity <95% r.h.

Standards

Test standards AS/NZS 3350.2.80:

1998 Amdts 1-3

"Electrical Fan"

Test Report no SD2446

EMC Compliance This is a Level One

product with an C frame motor that has a very low risk of causing EMC

Interference

General

Free Air Fan Performance
Installed decibel rating

326m³/ hr 90.6L/sec

47DB

Ordering

When ordering please give name and type,

Reference FV200D

Barcode 942000490003-7

Technical Data

Power Supply 230 VAC

Power consumption max. 0.38 Amps Supply Line fusing max. 10A For solid wires 2 x 1.5mm²

Motor 230-240VAC 50Hz

0,4Amp

Motor insulation class

Total motor wattage Motor protection 42Watts Impendence

Total product wattage protected 42 watts