## DATA SHEET



### MV457-4E 40° VAR. SPEED 1Ø – CFM 457mm Axial Kitchen Exhaust Roof Fan

MV models are high capacity roof mounted axial exhaust fans they are kitchen exhaust fans. The all metal fan casing provides a long lasting and robust construction. Suitable for high temperature kitchen exhaust systems.

Suitable for high temperature kitchen exhaust systems

Mountings: 462mm spigot off bottom of fan unit



# SPECIFICATIONS MV457-4E 40° VAR. SPEED 240V Kitchen Exhaust Roof Fan 4 Pole & Controller Motor: 230-240VAC 50Hz 1 Phase 4.5 Amp Full Load Current 1440 RPM Aerofoil adjustable pitch impellers Performance tests are in accordance with BS848 Part 1 (1980) and AS2936 - 1987 Total Motor Wattage: 750 Watts Sound level at 3m [dB(A)] Free Field: 59 Fully weather proof galvanized steel ventilated housing with grease trap connection Free Air Fan Performance: 3400 l/sec @ 40° (Speed controller supplied with fan) Impellor Diameter: 450mm diameter

Feati	ıres	Benefits					
<ul> <li>Motors have excellent speed</li> </ul>	control characteristics	0 (	Can be regulated down to 20-30% of full speed.				
<ul> <li>Sealed for life ball bearing m</li> </ul>	otors	0 5	Suitable for high temperature kitchen exhaust systems				
o The units are fully assembled		0 1	This allows quick and easy installation on site				
o Tops can be powder coated in	f required	o F	ans can be matched to fit your colour scheme				
Accessories Available			o Tubes, Roof Flashings, Tube Silencers all available				
o 1 Year Warranty							







# DATA SHEET



## **DIMENSIONS & ELECTRICAL DATA**



Product Code		Ø	Weight (kg)
	MV457-4E 40° VAR. SPEED 240V	462Ø	40



Ī			220-240V / 50Hz / 1Ø			Inlet Sound Power Level in dB re 10 pW								
	Product Code	Speed	Motor Rating (kw)	Full Load Current (at 230V) (A)	Speed Controller	Sound Pressure Levels	63	125	250	500	1K	2K	4K	8K
	MV457-4E	1440	0.75	4.5	MSC1200	59	48	59	74	73	74	72	69	64

Sound pressure levels quoted are average dBA at 3m distance over a sphere, under free field conditions and are presented for comparative purposes only.

